


TOK®-Band SK N2



Product Information



Special advantages:



Excellent adhesion and elasticity at -10 °C (14 °F).



Cold processed – no burner required.



No primer required.



Fulfils all requirements of ZTV Fug-StB 15.



Processing temperature from 0 °C to +35 °C (from +32 °F to +95 °F).

High-flexibility self-adhesive bitumen joint tape for joints and seams in asphalt road construction.

DEKOTEC GmbH stands for experience, quality and reliability in the field of corrosion prevention and sealing technology. The success is based on the development of the Petrolatum-Tape which was already developed in 1927 as the first product worldwide for passive corrosion prevention of pipelines. We establish and guarantee the highest quality standards with technically trend-setting products. Research, development and production take place exclusively in Germany. Our employees are continuously implementing safe and individual solutions in a personal cooperation with the customer.

Description

TOK®-Band SK N2 is a high-quality bitumen joint tape made from polymer-improved road bitumen with exceptional stretch and adhesion properties. **TOK®-Band SK N2** has a homogeneous full-surface adhesive coating on one side (smooth side), and can therefore be applied to "cold" joint edges

quickly and safely, without the use of a gas burner. **TOK®-Band SK N2** can be applied without primer to properly prepared edges that are clean, dry and free of dust. The slightly profiled (wavy) side of the bitumen tape is the side without an adhesive coating. This side will later form the base

for the "hot" asphalt mix.

If necessary, the optional primer **TOK®-SK Primer** can be used to boost the adhesion of **TOK®-Band SK N2** to the joint edge.

Usage

TOK®-Band SK N2 is ideal for sealing joints in asphalt road construction applications that are subject to special or demanding requirements. One example is **railway track construction**, where the joints on the rails have to cope with a great deal of

movement. Thanks to its high flexibility, the tape is also ideal for use at low temperatures, where conventional bitumen joint tapes would be too stiff for easy application. When used in conjunction with **TOK®-SK Primer**, the product boasts an exceptional

stretch capacity of **≥33%** at **-10°C (+14°F)**. Even at temperatures as low as **-20°C (-4°F)**, the adhesion and elasticity requirements specified for bitumen joint tape in **TL Fug-StB 15** are satisfied or exceeded.

Typical product properties (test results in accordance with TL Fug-StB)

Test	Unit	Typical results range	Requirement
Softening point (Ring&Ball method)	°C/°F	> +100 (+212)	> +90 (+194)
Cone penetration	0.1 mm	20–50	20–50
Recovery	%	10–30	10–30
Cold bending behaviour	°C/°F	≤ ±0 (+32)	≤ ±0 (+32)
Stretch and adhesive strength	% / N/mm ²	≥ 10 / ≤ 1.0	≥ 10 / ≤ 1.0

Application

Weather conditions:

In accordance with ZTV Fug-StB, bitumen joint tapes may only be applied in dry weather and when the surface temperature of the asphalt is at least +5°C (+41°F).

At temperatures between 0°C and +5°C (+30°F and +41°F), the product may only be applied if additional measures are taken (e.g. preheating of edges).

Requirements for connection edges:

In accordance with ZTV Fug-StB, the following basic requirements apply: Edge surfaces must be solid, even and straight for the successful application of bitumen joint tape.

The connection edges must be bevelled, precision-milled or cut, or assembled using ready-made components.

They must be free of dirt. Rust particles on steel components must be removed. Any residual dirt left adhering to the surface must be removed with a wire brush or compressed air. The edges must be dry.

Use of TOK®-Band SK N2:

If all of the requirements for connection edges are fully satisfied, **TOK®-Band SK N2** may be applied to the edge without primer. The relevant test results in accordance with TL/TP Fug-StB are available.

If necessary, you can optimise the adhesion of the bitumen joint tape to the edge, and ensure that the adhesion and stretch requirements for hot pouring compounds are met in accordance with ZTV Fug-StB 15, by also applying **TOK®-SK Primer**.

In summer, the drying time of **TOK®-SK Primer** is just 3 to 5 minutes, dependent on weather conditions, allowing further work to start quickly.

Application:

TOK®-Band SK N2 is applied to the prepared connection edge with the adhesive layer (smooth side) facing upwards.

The anti-adhesive paper should be removed just before the tape is laid.

The adhesive surface (smooth side) of the

laid **TOK®-Band SK N2** is pressed onto the connection edge by hand or using a tool.

ZTV Fug-StB 15 – bitumen joint tapes:

In accordance with ZTV Fug-StB, bitumen joint tape must be laid with a 5-mm protrusion on rolled asphalt surface layers, so that a so-called "rivet head" is produced when rolling the asphalt. This forms an additional seal on the surface and provides a clean "closure".

In cast asphalt surfaces, the joint tape is laid flush to the edge.

The width of the joint tape must be at least **10 mm**.

In accordance with ZTV Fug-StB and TL Fug-StB, the quality of the material must be monitored by a third party and verified by placing an approval label on the packaging.

Ordering information and packaging

TOK®-Band SK N2 is supplied on rolls. The rolls are sorted by cross-section size,

separated using silicone paper and delivered in boxes measuring (w x d x h) 370 mm x 370 mm x 160 (or 144) mm.

30 boxes are packed on one euro pallet (800 x 1200 mm).

Profile [HxW]	Article number*	m/box	m/pallet
25x8		60	1.800
30x10		40	1.200
35x8		48	1.440
35x10		40	1.200
40x8		36	1.080
40x10		30	900

*on request

Storage

Store dry and protected from frost, in normal ambient temperature conditions (ideally 15–20°C/ 59–68°F); do not stack anything on top of the boxes.

In these conditions, **TOK®-Band SK N2** can be stored in its sealed original packaging for at least two years from the date of manufacture.

DEKOTEC GmbH

Felderstrasse 24 | 51371 Leverkusen | Germany
Phone: +49 214 2602-0 | info@dekotec.com
www.dekotec.com

Our product information, application recommendations and other printed publications provide advice to the best of our knowledge and indicate our level of knowledge at the time of printing. The content is not legally binding. Therefore, no liability is assumed for incorrect and missing advice. The applicator is obliged to check the suitability and possibility of application for the intended purpose. Unless otherwise specified, all of the brands named are trademarks, at least registered in Germany, which are protected by law.

Only our general terms and conditions of sale, which you will find at www.dekotec.com, apply. This is a translation from the original German product information. In case of any discrepancy or any dispute arising on the interpretation, the German text of the respective German product information, shall be decisive. The legal relationship shall be governed by German law.

08.2022